






## STIRNRÄDER / ZAHNRÄDER ROSTFREI

### MODUL 2

Eingriffswinkel  $20^\circ$

| A  | B  |
|----|----|
| 35 | 20 |





Werkstoff: Edelstahl 1.4305 // Verzahnung gerade // ab Zähnezahl 80 ohne Nabe

| Z  | Artikelnr. | de    | dp    | dm | D1 | kg   |
|----|------------|-------|-------|----|----|------|
| 12 | 403020012  | 28,0  | 24,0  | 18 | 10 | 0,08 |
| 13 | 403020013  | 30,0  | 26,0  | 20 | 10 | 0,10 |
| 14 | 403020014  | 32,0  | 28,0  | 22 | 10 | 0,12 |
| 15 | 403020015  | 34,0  | 30,0  | 24 | 10 | 0,14 |
| 20 | 403020020  | 44,0  | 40,0  | 30 | 10 | 0,26 |
| 24 | 403020024  | 52,0  | 48,0  | 35 | 12 | 0,36 |
| 25 | 403020025  | 54,0  | 50,0  | 35 | 12 | 0,39 |
| 30 | 403020030  | 64,0  | 60,0  | 40 | 14 | 0,55 |
| 40 | 403020040  | 84,0  | 80,0  | 50 | 14 | 0,97 |
| 50 | 403020050  | 104,0 | 100,0 | 70 | 16 | 1,62 |
| 60 | 403020060  | 124,0 | 120,0 | 70 | 16 | 2,16 |
| 80 | 403020080  | 164,0 | 160,0 | —  | 20 | 3,09 |

### MODUL 2,5

Eingriffswinkel  $20^\circ$

| A  | B  |
|----|----|
| 45 | 25 |



Werkstoff: Edelstahl 1.4305 // Verzahnung gerade

| Z  | Artikelnr. | de    | dp    | dm  | D1 | kg   |
|----|------------|-------|-------|-----|----|------|
| 12 | 403025012  | 35,0  | 30,0  | 22  | 10 | 0,17 |
| 13 | 403025013  | 37,5  | 32,5  | 25  | 10 | 0,21 |
| 14 | 403025014  | 40,0  | 35,0  | 28  | 10 | 0,25 |
| 15 | 403025015  | 42,5  | 37,5  | 30  | 10 | 0,30 |
| 20 | 403025020  | 55,0  | 50,0  | 40  | 12 | 0,54 |
| 24 | 403025024  | 65,0  | 60,0  | 45  | 14 | 0,74 |
| 25 | 403025025  | 67,5  | 62,5  | 50  | 14 | 0,85 |
| 30 | 403025030  | 80,0  | 75,0  | 55  | 14 | 1,18 |
| 40 | 403025040  | 105,0 | 100,0 | 70  | 16 | 2,06 |
| 50 | 403025050  | 130,0 | 125,0 | 80  | 20 | 3,07 |
| 60 | 403025060  | 155,0 | 150,0 | 100 | 20 | 4,57 |